

## Hand Knobs

**Knob Cast Iron / Stainless Steel / Aluminum,  
Threaded Stud Stainless Steel**

### SPECIFICATION

#### Types

- Type **AM**: Hand knobs Aluminum, matte finish (tumbled), threaded stud stainless steel
- Type **AP**: Hand knobs Aluminum, polished, threaded stud stainless steel
- Type **ES**: Hand knobs Stainless steel precision casting AISI CF-8, threaded stud stainless steel
- Type **A4P**: Hand knobs Stainless steel precision casting AISI 316

#### Threaded stud

Stainless steel AISI 303

Screwed in and secured by a cross-dowel

#### Knob

- Aluminum
  - Matte finish (tumbled) **AM**
  - Polished **AP**
- Stainless steel precision casting AISI CF-8 **ES**  
Matte shot-blasted

#### Stainless steel precision casting AISI 316 A4P

Polished



### INFORMATION



Hand knobs GN 6335.5 satisfy the dimensions of the DIN 6335 (see page 234) Type L but differ in terms of their non-scooping geometry, which makes cleaning easier and helps prevent possible build-up of dirt.

They are suitable for areas with special hygiene requirements and, thanks to the material used, for applications in highly corrosive environments.

### TECHNICAL INFORMATION

- Stainless Steel Characteristics (see page A26)





GN 6335.5-AM

Description	d1	d2	Length l ≈	d3	h1	h2	△
GN 6335.5-AM-40-M8-20	40	M 8	20	14	25	13	34
GN 6335.5-AM-40-M8-25	40	M 8	25	14	25	13	36
GN 6335.5-AM-40-M8-30	40	M 8	30	14	25	13	38
GN 6335.5-AM-40-M8-40	40	M 8	40	14	25	13	40
GN 6335.5-AM-50-M10-20	50	M 10	20	18	32	18	63
GN 6335.5-AM-50-M10-25	50	M 10	25	18	32	18	65
GN 6335.5-AM-50-M10-30	50	M 10	30	18	32	18	68
GN 6335.5-AM-50-M10-45	50	M 10	45	18	32	18	75
GN 6335.5-AM-50-M10-55	50	M 10	55	18	32	18	78
GN 6335.5-AM-63-M12-30	63	M 12	30	20	40	23	104
GN 6335.5-AM-63-M12-40	63	M 12	40	20	40	23	111
GN 6335.5-AM-63-M12-50	63	M 12	50	20	40	23	118

GN 6335.5-AP

Description	d1	d2	Length l ≈	d3	h1	h2	△
GN 6335.5-AP-40-M8-20	40	M 8	20	14	25	13	34
GN 6335.5-AP-40-M8-25	40	M 8	25	14	25	13	36
GN 6335.5-AP-40-M8-30	40	M 8	30	14	25	13	38
GN 6335.5-AP-40-M8-40	40	M 8	40	14	25	13	40
GN 6335.5-AP-50-M10-20	50	M 10	20	18	32	18	63
GN 6335.5-AP-50-M10-25	50	M 10	25	18	32	18	65
GN 6335.5-AP-50-M10-30	50	M 10	30	18	32	18	68
GN 6335.5-AP-50-M10-45	50	M 10	45	18	32	18	75
GN 6335.5-AP-50-M10-55	50	M 10	55	18	32	18	78
GN 6335.5-AP-63-M12-30	63	M 12	30	20	40	23	104
GN 6335.5-AP-63-M12-40	63	M 12	40	20	40	23	111
GN 6335.5-AP-63-M12-50	63	M 12	50	20	40	23	118

GN 6335.5-ES

STAINLESS STEEL

Description	d1	d2	Length l ≈	d3	h1	h2	△
GN 6335.5-ES-40-M8-20	40	M 8	20	14	25	13	74
GN 6335.5-ES-40-M8-25	40	M 8	25	14	25	13	76
GN 6335.5-ES-40-M8-30	40	M 8	30	14	25	13	78
GN 6335.5-ES-40-M8-40	40	M 8	40	14	25	13	82
GN 6335.5-ES-50-M10-20	50	M 10	20	18	32	18	136
GN 6335.5-ES-50-M10-25	50	M 10	25	18	32	18	139
GN 6335.5-ES-50-M10-30	50	M 10	30	18	32	18	142
GN 6335.5-ES-50-M10-45	50	M 10	45	18	32	18	151
GN 6335.5-ES-50-M10-55	50	M 10	55	18	32	18	158
GN 6335.5-ES-63-M12-30	63	M 12	30	20	40	23	254
GN 6335.5-ES-63-M12-40	63	M 12	40	20	40	23	263
GN 6335.5-ES-63-M12-50	63	M 12	50	20	40	23	271

GN 6335.5-A4P

STAINLESS STEEL

Description	d1	d2	Length l ≈	d3	h1	h2	△
GN 6335.5-A4P-32-M6-12	32	M 6	12	12	20	9	43
GN 6335.5-A4P-32-M6-16	32	M 6	16	12	20	9	44
GN 6335.5-A4P-32-M6-20	32	M 6	20	12	20	9	45
GN 6335.5-A4P-32-M6-25	32	M 6	25	12	20	9	46
GN 6335.5-A4P-40-M8-20	40	M 8	20	14	25	13	74
GN 6335.5-A4P-40-M8-25	40	M 8	25	14	25	13	76
GN 6335.5-A4P-40-M8-30	40	M 8	30	14	25	13	78
GN 6335.5-A4P-40-M8-40	40	M 8	40	14	25	13	82
GN 6335.5-A4P-50-M10-20	50	M 10	20	18	32	18	136
GN 6335.5-A4P-50-M10-25	50	M 10	25	18	32	18	139
GN 6335.5-A4P-50-M10-30	50	M 10	30	18	32	18	142
GN 6335.5-A4P-50-M10-45	50	M 10	45	18	32	18	151
GN 6335.5-A4P-50-M10-55	50	M 10	55	18	32	18	158
GN 6335.5-A4P-63-M12-30	63	M 12	30	20	40	23	254
GN 6335.5-A4P-63-M12-40	63	M 12	40	20	40	23	263
GN 6335.5-A4P-63-M12-50	63	M 12	50	20	40	23	271



Clamping knobs 2