



## Modular roller tracks



ele:roll®



DESIGNED  
FOR ENGINEERING

# Modular roller tracks ELEROLL

---

Modular roller tracks for idle handling.


They can be used to create sliding and containing benches suitable for several applications in different fields: feeding and discharging benches in construction machinery, storage and picking systems, packaging machinery, etc.

## Modularity

---

The roller track can be easily assembled by fixing the roller or ball elements inside the appropriate aluminium anodised profiles.

The particular section of the profile allows the snap-in assembly of the roller and ball elements into the profile without the need for screws or other fasteners.



## Substitution


---

The roller and ball elements may be removed and replaced quickly and easily, without disassembling the entire roller track. The aluminium profile can be reused.

## Sliding and quiet operation

---

The features of the materials of the rollers / balls and relative holders allow friction to be minimised and there is no need for lubrication maintenance.



## High load capacity

---

The roller track ensures a high load capacity, thanks to a maximum capacity for single roller of 360N (PA rollers) and 150N (TPU rollers).

## High impact strength

---

The roller elements are characterised by a high capacity to absorb shocks due to drop of material on the roller track.

## Handling of delicate materials

---

The thermoplastic (TPU) polyurethane rollers, anti-scratch and antitrace material, are also suitable for handling delicate materials such as glass and wood.

## Omnidirectional handling

---

The technopolymer acetal resin based (POM) balls allow the easy handling of the material in any direction.

# Modular roller tracks ELEROLL

	Profile	Roller and ball elements	Load capacity #	
			Distributed load, roller fully supported	Concentrated load on a single roller / ball
	RLT-AL	RLT-U-PA	13330 N/m	360 N
		RLT-U15-PA	13330 N/m	200 N
	RLT-AL	RLT-U-TPU	5550 N/m	150 N
	RLT-AL	RLS-U-POM	850 N/m	30 N

The data in the table refer to the handling of materials with a stiffness such as to keep flat the contact surface with the rollers. Otherwise the values may be lower.

**# RLT-U-PA:** load values produce an elastic deformation such as to prevent the regular rotation of the rollers, which come into contact with the ribs of the aluminum profile. At these load values however, no permanent deformation of the material occurs.




**# RLT-U-TPU:** load values higher than those reported in the table produce a deformation such as to prevent the rotation of the rollers, that come into contact with the ribs of the aluminum profile. Loads higher than 100N for a single roller cause a reduction in the rolling resistance.

**# RLT-U15:** the load values exceeding the ones indicated in the table determine a reduction in the rolling resistance. However, no significant permanent deformation of the material occurs to these load values.

**# RLS-U-POM:** load values that limit the smoothness of the balls inside its support, at low sliding speeds. At these load values, however, no permanent deformation of the material occurs. For higher sliding speeds, it is necessary to refer to the chart at the side.


## LOAD CAPACITY

LOAD CONCENTRATED IN THE CENTRE, ROLLER TRACK SUPPORTED IN TWO POINTS



P: applied in the centre of the roller track, the load value generates an elastic deflection of the aluminum profile beyond which the product functionality may be compromised. At this load value, however, no permanent deformation of the material occurs. L = distance between supports. f = arrow.

## IMPACT STRENGTH



# Modular roller tracks ELEROLL




## RLT-U

Roller elements

Acetal resin based (POM) technopolymer roller holder, black colour.

RLT-U-PA: polyamide based (PA) technopolymer rollers, black colour.

RLT-U-TPU: thermoplastic (TPU) polyurethane rollers, hardness 92 Shore A, grey colour.




## RLT-U15

Roller elements

Acetal resin based (POM) technopolymer roller holder, black colour.

RLT-U15-PA: polyamide based (PA) technopolymer rollers, black colour.

RLT-U15-TPU: thermoplastic (TPU) polyurethane rollers, hardness 92 Shore A, grey colour.





## RLS-U

Ball elements

Balls: acetal resin based (POM) technopolymer, white colour.

Ball holder: polyamide based (PA) technopolymer, black colour.




## RLT-AL

Aluminium profiles

The profile can hold up to 11 RLT-U roller elements or RLS-U ball elements.


The profile ensures a high resistance to bending under load, and the assembly of the roller tracks without the need for other supports.



## RLT-H

Headers


RLT-HJ header serves to bind tightly two rollers by engaging them. RLT-HE header is the end-element of roller tracks. In addition to being an aesthetic element, the headers represent a safety element for the operator's hands and the handled material.



## RLT-CE

Containment edge


RLT-CE containment edge is used for the lateral containment of products handled on roller tracks. It is snap-in assembled on RLT-AL aluminum profiles without the need for screws or other fasteners. It can also be mounted to the roller track already fixed.



## RLT-B

Brakes


RLT-B brakes allow to slow down and/or stop packages handled on roller tracks. The brakes are snap-in assembled on RLT-U roller elements without the need for screws or other fasteners.



## RLT-M

Bracket and support

The bracket and the support facilitate the mounting of roller tracks on machines and other supporting structures.



## Roller elements for ELEROLL roller tracks

Technopolymer and polyurethane

### STANDARD EXECUTIONS

- Acetal resin based (POM) technopolymer roller holder, black colour.
- **RLT-U-PA**: polyamide based (PA) technopolymer rollers, black colour. Working temperature +90°/-20°C.
- **RLT-U-TPU**: thermoplastic (TPU) polyurethane rollers, hardness 92 Shore A, grey colour. Working temperature +70°/-20°C.

### FEATURES AND APPLICATIONS

- The roller elements, suitably fixed inside the RLT-AL aluminum profiles (Fig. 1) create modular roller tracks for idle handling (both as sliding or containing surfaces), suitable for several applications in different fields: feeding and discharging benches in construction machinery, storage and picking systems, packaging machinery, etc..
- RLT-U-PA roller elements are also suitable for handling heavy packages, RLT-U-TPU roller elements, with rollers in anti-scratch material, allow the handling of delicate materials such as glass and wood.
- The low friction coefficient between the roller and the roller holder eliminates the need for lubrication maintenance.
- The particular section of RLT-AL profile allows the snap-in assembly of the roller elements into the profile without the need for screws or other fasteners (Fig.1). Therefore the roller elements may be quickly and easily removed and replaced, without disassembling the entire roller track.
- The roller elements are divisible in correspondence of predefined sections (Fig.2) so as to create roller tracks of the precise required length.

### TECHNICAL DATA

See: ELEROLL Modular roller tracks (on page 1108).



### SPECIAL EXECUTIONS ON REQUEST

Rollers in different colour (for example red, yellow, green for the setting up of assembly lines and dynamic warehouses according to Kanban criteria).



FMA design

ele:roll®



#### RLT-U-PA

Code	Description	⚖️
429806	RLT-U-PA	106

#### RLT-U-TPU

Code	Description	⚖️
429811	RLT-U-TPU	114

## Roller elements for ELEROLL roller tracks

For packages with reduced size, technopolymer

### STANDARD EXECUTIONS



- Acetal resin based (POM) technopolymer roller holder, black colour.
- **RLT-U15-PA**: polyamide based (PA) technopolymer rollers, black colour. Working temperature +90°/-20°C.
- **RLT-U15-TPU**: thermoplastic (TPU) polyurethane rollers, hardness 92 Shore A, grey colour. Working temperature +70°/-20°C.

### FEATURES AND APPLICATIONS

- The roller elements, suitably fixed inside the RLT-AL aluminum profiles (Fig. 1) create modular roller tracks for idle handling (both as sliding or containing surfaces), suitable for several applications in different fields: feeding and discharging benches in construction machinery, storage and picking systems, packaging machinery, etc..
- RLT-U15 roller elements are suitable for handling of packages with reduced weight and size. The smaller diameter of the rollers ensures a reduction in vibrations and consequently a lower noise during handling of packages.
- RLT-U15-TPU roller elements, with rollers in anti-scratch material, allow the handling of delicate materials such as glass and wood.
- The low friction coefficient between the roller and the roller holder eliminates the need for lubrication maintenance.
- The particular section of RLT-AL profile allows the snap-in assembly of the roller elements into the profile without the need for screws or other fasteners (Fig.1). Therefore the roller elements may be quickly and easily removed and replaced, without disassembling the entire roller track.
- The roller elements are divisible in correspondence of predefined sections (Fig.2) so as to create roller tracks of the precise required length.
- All the accessories of ELEROLL series can also be used with the RLT-U15 roller elements, except for RLT-B brakes.



FM design **ele:roll**



Code	Description	Δ
429807	RLT-U15-PA	102
429808	RLT-U15-TPU	109

## Ball elements for ELEROLL roller tracks

### Technopolymer

#### BALLS

Acetal resin based (POM) technopolymer, white colour.

#### BALL HOLDER

Polyamide based (PA) technopolymer, black colour.

#### FEATURES AND APPLICATIONS

- The ball elements, suitably fixed within the RLT-AL aluminum profiles (Fig. 1) create modular roller tracks for idle omnidirectional handling.
- The ball elements can be combined with RLT-U roller elements for various applications in different fields: feeding and discharging benches in construction machinery, storage and picking systems, packaging machinery, etc.
- The low friction coefficient between the ball and the ball holder eliminates the need for lubrication maintenance.
- The particular section of RLT-AL profile allows the snap-in assembly of the ball elements into the profile without the need for screws or other fasteners (Fig.1).
- The ball elements are divisible in correspondence of predefined sections (Fig.2) so as to create roller tracks of the precise required length.
- The balls may be removed and replaced without disassembling the entire roller track, by using a common screwdriver in the appropriate notch cut into the ball holder (Fig. 3).



#### TECHNICAL DATA

See: ELEROLL Modular roller tracks (on page 1108).



FMA design

ele:roll®



Code	Description	⚖
429801	RLS-U-POM	151

## Profiles for ELEROLL roller tracks

### Aluminium

#### STANDARD EXECUTIONS

- **RLT-AL-AN**: anodised aluminium, natural colour.
- **RLT-AL-BL**: aluminium, natural colour.
- **RLT-AL-AN-SL**: anodised aluminium, natural colour, slotted holes.

#### FEATURES AND APPLICATIONS

The profile can hold up to 11 RLT-U, RLT-U15 roller elements or RLS-U ball elements. The particular section of the profile allows the interlocking fixing of the roller and ball elements without the need for screws or other fasteners.

The profile ensures a high resistance to bending under load, and the assembly of the roller tracks, even in case of not complete support (Fig. 1), without the need for other supports.



#### SPECIAL EXECUTIONS ON REQUEST

Profiles with length different from the standard executions (maximum length 2970 mm).

#### ASSEMBLY INSTRUCTIONS

Fix the profile to the supporting structure with screws of suitable size and number for the specific application, by making, if necessary, appropriate holes in the base of the profile.

The profile can be mounted in two points of support (Fig. 1) or in complete support (Fig. 2).

For the drainage of any fluids that can collect inside the profile (for example in case of applications on machines and equipment whose parts must be frequently cleaned by using water jets, for hygienic reasons) it is recommended, if necessary to make holes of appropriate size and shape in the base of the profile.






Fig.1

Fig.2



#### TECHNICAL DATA

See: ELEROLL Modular roller tracks (on page 1108).



#### RLT-AL-AN

#### RLT-AL-BL

#### RLT-AL-AN-SL

Code	Description	Code	Description	Code	Description	L	Δ
429900-0270	RLT-AL-270-AN	429920-0270	RLT-AL-270-BL	429910-0270	RLT-AL-270-AN-SL	270	123
429900-0540	RLT-AL-540-AN	429920-0540	RLT-AL-540-BL	429910-0540	RLT-AL-540-AN-SL	540	247
429900-0810	RLT-AL-810-AN	429920-0810	RLT-AL-810-BL	429910-0810	RLT-AL-810-AN-SL	810	370
429900-1080	RLT-AL-1080-AN	429920-1080	RLT-AL-1080-BL	429910-1080	RLT-AL-1080-AN-SL	1080	495
429900-1350	RLT-AL-1350-AN	429920-1350	RLT-AL-1350-BL	429910-1350	RLT-AL-1350-AN-SL	1350	618
429900-1620	RLT-AL-1620-AN	429920-1620	RLT-AL-1620-BL	429910-1620	RLT-AL-1620-AN-SL	1620	740
429900-1890	RLT-AL-1890-AN	429920-1890	RLT-AL-1890-BL	429910-1890	RLT-AL-1890-AN-SL	1890	865
429900-2160	RLT-AL-2160-AN	429920-2160	RLT-AL-2160-BL	429910-2160	RLT-AL-2160-AN-SL	2160	990
429900-2430	RLT-AL-2430-AN	429920-2430	RLT-AL-2430-BL	429910-2430	RLT-AL-2430-AN-SL	2430	1110
429900-2700	RLT-AL-2700-AN	429920-2700	RLT-AL-2700-BL	429910-2700	RLT-AL-2700-AN-SL	2700	1235
429900-2970	RLT-AL-2970-AN	429920-2970	RLT-AL-2970-BL	429910-2970	RLT-AL-2970-AN-SL	2970	1360

## Headers for ELEROLL roller tracks

### Technopolymer

#### MATERIAL

Polyamide based technopolymer (PA), black colour.

#### STANDARD EXECUTIONS

- **RLT-HJ**: joining header.
- **RLT-HE**: end header.

#### FEATURES AND APPLICATIONS

RLT-HJ header serves to bind tightly two ELEROLL rollers by engaging them (Fig. 1).

RLT-HE header is the end-element of ELEROLL roller tracks (Fig. 2). In addition to being an aesthetic element, the headers represent a safety element for the operator's hands and the handled material.




#### MOUNTING

Assemble the headers to the end of RLT-AL aluminum profile by means of two UNI 6954 Ø 2,9 x13 self-tapping screws (included in the supply).



FMdesign

ele:roll®



RLT-HJ		
Code	Description	⚖
429823	RLT-HJ	4

RLT-HE		
Code	Description	⚖
429813	RLT-HE	6

## Containment edge for ELEROLL roller tracks

Polycarbonate

### MATERIAL

Polycarbonate (PC), black colour.

### FEATURES AND APPLICATIONS


Realized to be used with RLT-U and RLT-U15 roller elements, RLT-CE containment edge needs for the lateral containment of light products handled on ELEROLL roller tracks (Fig.1).

For the containment of medium-heavy materials refer to the RLT-M series (Fig. 3).

The edge is snap-in assembled on RLT-AL aluminum profiles without the need for screws or other fasteners (Fig.2). It can also be mounted to the roller track already fixed.





Fig.1



FMA design

ele:roll®

Fig.2



Code	Description	⚖️
429826	RLT-CE	34

## Brakes for ELEROLL roller tracks

Polycarbonate

### MATERIAL

Polycarbonate (PC), black colour.

### STANDARD EXECUTIONS

- **RLT-BR**: brake for RLT-U roller elements.
- **RLT-BRS**: brake for RLT-U roller elements with stop device.

### FEATURES AND APPLICATIONS

RLT-B brakes allow to slow down and/or stop packages handled on ELEROLL roller tracks.

The brakes are snap-in assembled on RLT-U roller elements without the need for screws or other fasteners.

RLT-BR brake can be assembled on the upper side of RLT-U-PA and RLT-U-TPU roller elements (Fig. 1) or on the lower side of the RLT-U-TPU roller elements (Fig. 2).




FM design

ele:roll®



Fig.1

Fig.2



RLT-BR

RLT-BRS



RLT-BR

Code	Description	
429836	RLT-BR	12

RLT-BRS

Code	Description	
429831	RLT-BRS	14

## Bracket and support for ELEROLL roller tracks

### Technopolymer

#### MATERIAL

Polyamide based (PA) technopolymer, black colour.

#### STANDARD EXECUTIONS

- **RLT-MB**: bracket.
- **RLT-MS**: support.
- **RLT-MS-A12**: support with connecting rod and M6 cylindrical head screw with hexagon socket.

#### FEATURES AND APPLICATIONS

The bracket and the support facilitate the mounting of ELEROLL roller tracks on machines and other supporting structures.

#### MOUNTING

The bracket and the support are equipped with dowels that are housed in the slots in the lower side of RLT-AL aluminum profiles (Fig. 1) and in special counterseats on the same support for the combination of more supporting elements (Fig. 2).


RLT-MB bracket is compatible with profiles having a slot of 8 mm width (Fig.4).

The bracket and the support allow to mount ELEROLL roller tracks in different configurations. Some examples are shown in Fig.1, Fig.2 and Fig.3.




FMA design


ele:roll®



RLT-MB



RLT-MS



RLT-MS-A12





Fig.4

RLT-MB

RLT-MS

RLT-MS-A12



#### RLT-MB

Code	Description	⚖️
429841	RLT-MB	35

#### RLT-MS

Code	Description	⚖️
429846	RLT-MS	49

#### RLT-MS-A12

Code	Description	⚖️
429848	RLT-MS-A12	145



Find out more on [elesa-ganter.in](http://elesa-ganter.in)

ELESA AND GANTER INDIA PVT LTD  
A-54, SECTOR-83  
Noida - 201305 (UP)  
India  
+91 120 4726666  
[info@elesa-ganter.in](mailto:info@elesa-ganter.in)  
**elesa-ganter.in**



**DESIGNED  
FOR ENGINEERING**